# HP DesignJet T2600 Multifunction Printer series



### Engineered for collaboration – Turn your workgroups into highly efficient teams



#### Seamless experience – Designed for all

- Radically simple experience with a smart 396.2 mm (15.6 in) interface and the easiest PDF printing with HP Click.
- Engage in a collaborative workstyle with teams quickly accessing shared folders to print and scan.
- Empower your workforce. Easily print and share jobs from the cloud with your mobile device and HP Smart app.
- Fits your workplace with the most compact footprint and most quiet operation, with up to 87% less noise.

#### Unleash performance – To turn design into delivery

- Showcase design versatility from precise line drafts to boldly coloured 3D renders, with HP Bright Office Inks
- Provide the highest accuracy and display the finest details with the unique Adobe PDF Print Engine.4
- Meet deadlines with the fastest speed up to 180 D/hr, the only automatic print stacking<sup>3</sup>, and dual rolls.5
- Easily digitise your projects with automated scanning, user-centric guicksets, and postediting capabilities.

#### Secure – World's most secure large-format printer<sup>6</sup>

- Rely on the best network protection with features like HP Secure Boot and whitelisting.<sup>6</sup>
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

#### For more information, please visit http://www.hp.com/go/designjett2600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

<sup>6</sup> Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019

<sup>&</sup>lt;sup>1</sup> Compared to Canon Direct Print & Share and based on "One Click Print." Once image is selected, one-click printing when printing the entire file without any modifications to the print settings. Applicable to PDF, JPEG, TIFF, DWF, HP-GL/2 files.

<sup>&</sup>lt;sup>2</sup> Using Lightweight Directory Access Protocol (LDAP). <sup>3</sup> Based on comparable large-format inkjet printers under €12,000 as of December, 2018. IDC figures show that Canon, Epson, and HP combine for 98% share of this printing category worldwide as of Q3, 2018. Most compact footprint calculated using all devices in "Operation mode" with an Open Basket and the arm of the Screen (front panel) spread out to enable user interaction and the scanner lifted on the Canon TX 3000 T36 MFP and the Epson SC-T5200 MFP to enable top media loading. Most quiet according to internal HP testing of sound pressure level during operating mode (plain paper, line drawing, Normal mode) compared to published specification of competitive printers. Percentage calculations of noise based on lineal units vs. Canon TX-3000 published spec of 51dB(A). Fastest print speed based on sustained printing speeds. Only automatic print

Specification of competitive printers, Percentage calculations of hose association and automatic print stacking based on unicity of the integrated stacker versus competitive printers only offering basket or bin with stacking position.
<sup>4</sup> Requires purchase of the HP DesignJet T2600 PostScript<sup>®</sup> models or optional HP DesignJet PostScript/PDF Upgrade Kit, Highest accuracy and finest details compared to printers without the embedded Adobe technology excluding RIP users, and based on internal HP testing with PDF files containing special forst, PANTONE<sup>®</sup> colors, smooth shading, overprint, and transparencies that can only be reproduced using the Adobe PDF Print Engine. The Adobe PDF Print Engine (APPE) is Adobe, high fidelity print platform. To learn more, visit http://www.adobe.com/products/pdfprintengine.
<sup>5</sup> Dual rolls included with HP DesignJet T2600dr multifunction printers only.

### Technical specifications

Print speed	180 A1/hr, 19.3 sec/A1 <sup>1</sup>
Print resolution	Up to 2400 x 1200 optimised dpi
Technology	HP Thermal Inkiet
Margins	Roll: 3 x 3 x 3 x 3 mm
nargins	Sheet: 3 x 22 x 3 x 3 mm
Ink types	Dye-based (C, M, Y, pK, G); pigment-based (mK)
Printheads	1 universal printhead
Line accuracy	±0.1% <sup>2</sup>
Minimum line width	0.02 mm (PDF addressable at 1200 dpi)
Multifunction capabilities	
Scan speed	Scan: Up to 7.62 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi)
	Copy: Up to 15.24 cm/sec (color, 200 dpi), up to 25.4 cm/sec (grayscale, 200 dpi)
Scan resolution	Up to 600 dpi
Scan format	JPEG, TIFF and multipage TIFF, PDF and multipage PDF <sup>3</sup>
Scan destinations	USB, shared network folder, printer HDD, email
Maximum scan width	914 x 8000 mm (JPEG); 610 x 15,000 mm (TIFF); 914 x 8000 mm (PDF) <sup>3</sup>
Thickness	0.8 mm
Media	
Handling	Sheet feed, automatic front-loading roll feed, smart roll switching <sup>4</sup> , integrated output stacker, media bin, automatic horizontal cutter Scanner: straight-through scan paper path for sheet and cardboard originals
Roll size	279 to 914 mm
Sheet size	210 x 279 to 914 x 1219 mm
Standard sheets	A4, A3, A2, A1, A0
Thickness	Up to 0.5 mm
Applications	Line drawings; Maps; Orthophotos; Presentations; Renderings
	128 GB (file processing) <sup>5</sup>
Memory Hard disk	
	500 GB self-encrypting
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootF/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP- TLS), DFS
Print languages (standard)	PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4
Printing paths	Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for MacOS and for iOS, HP Print for Chrome OS, HP Click, HP Smart App for iOS and Android
Drivers	PostScript Printer: Raster, PostScript and PDF drivers for Windows, AirPrint for macOS Non-PostScript Printer: Raster drivers for Windows, AirPrint for macOS
Security features	HP Secure Boot, Whitelisting, TPM, Role Based Access Control, LDAP and Kerberos authentication, SNMPv3, HTTPS, Secure-IPP, IPsec/Firewall, Certificates management, 802.1X, TLS 1.0/1.1/1.2, HP Web Jetadmin compatible, HP JetAdvantage Security Manager compatible, Secure Disk erase (DoD 5220.22-M), Secure File erase, self-encrypting HDD, encrypted PIN printing, Syslog security logging
Dimensions (w x d x h)	
Printer	1390 x 760 x 1240 mm
Shipping	1477 x 767 x 800 mm
Weight	
Printer	Single-roll: 106 kg, dual-roll: 109 kg
Shipping	Single-roll: 137 kg, dual-roll: 142 kg
What's in the barr	
	HP Designlet T2600 Multifuntion Printer, printer stand and media bin, 39.62 cm (15.6 in) touchscreen, spindle(s) <sup>b</sup> , printheads, introductory ink cartridges, user guide, power cords UD Click UD mobile oblicated in Schodreid support blue the UD Schot and for mobile. UD Nobile Jatafenie, UD LetAdvantae
HP Software and solutions	printheads, introductory ink cartridges, user guide, power cords
HP Software and solutions Environmental ranges	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantac Security Manager, HP SmartTracker (optional)
HP Software and solutions Environmental ranges Operating temperature	printheads, introductory ink cartridges, user guide, power cards HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35°C
HP Software and solutions Environmental ranges Operating temperature Operating humidity	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35%C 20 to 80% RH
HP Software and solutions Environmental ranges Operating temperature Operating humidity	printheads, introductory ink cartridges, user guide, power cards HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35°C
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35%C 20 to 80% RH
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35%C 20 to 80% RH
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantac Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantac Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep)
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep)
What's in the box HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power Consumption Requirements	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) <5.9 B(A) (operating), s4.9 B(A) (idle), <3.5 B(A) (sleep)
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power Consumption	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) <5.9 B(A) (operating), s4.9 B(A) (idle), <3.5 B(A) (sleep) 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off)
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power Consumption Requirements Certification	printheads, introductory ink cartridges, user guide, power cords HP (Citck, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantac Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) <5.9 B(A) (operating), 24.9 B(A) (idle), <3.5 B(A) (sleep) 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power Consumption Requirements Certification Safety	printheads, introductory ink cartridges, user guide, power cords HP Click, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantag security Manager, HP SmartTracker (optional) 5 to 35%C 20 to 80% RH -25 to 55%C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) <5.9 B(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) 5.9 B(A) (operating), s4.9 B(A) (idle), <17 dB(A) (sleep) 120 W (printing); < 36 W (ready); <1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max EU (LVD and EN 60950-1 compliant); Russia, Belarus, Khazakstan (EAC); Ukraine (UA)
HP Software and solutions Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound power Power Consumption Requirements	printheads, introductory ink cartridges, user guide, power cords HP (Citck, HP mobile, ePrint and iOS/Android support plus the HP Smart app for mobile, HP Web Jetadmin, HP JetAdvantac Security Manager, HP SmartTracker (optional) 5 to 35°C 20 to 80% RH -25 to 55°C 42 dB(A) (operating), 32 dB(A) (idle), <17 dB(A) (sleep) <5.9 B(A) (operating), 24.9 B(A) (idle), <3.5 B(A) (sleep) 120 W (printing); < 36 W (ready); < 1 W (< 10 W with embedded Digital Front End) (sleep); 0.3 W (off) Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A max

## Ordering information

3XB78A 3EK15A	HP DesignJet T2600 36-in PostScript Multifunction Printer HP DesignJet T2600dr 36-in PostScript Multifunction Printer
Accessories	···
5NB95A	HP SmartTracker USB for DesignJet
5NB95AAE CN538A	HP SmartTracker for DesignJet HP DesignJet 3-in Core Adapter
N7P47AA	HP USB 3.0 to Gigabit LAN Adapter
	inting supplies
33P06A 22V62A	HP 727 DesignJet Printhead HP 730 130-ml Cyan DesignJet Ink Cartridge
P2V63A	HP 730 130-ml Magenta DesignJet Ink Cartridge
P2V64A P2V65A	HP 730 130-ml Yellow DesignJet Ink Cartridge HP 730 130-ml Matte Black DesignJet Ink Cartridge
P2V66A	HP 730 130-ml Gray DesignJet Ink Cartridge
2V67A 2V68A	HP 730 130-ml Photo Black DesignJet Ink Cartridge HP 730 300-ml Cyan DesignJet Ink Cartridge
2V69A 2V70A	HP 730 300-ml Magenta DesignJet Ink Cartridge HP 730 300-ml Yellow DesignJet Ink Cartridge
2V71A	HP 730 300-ml Matte Black DesignJet Ink Cartridge
2V72A 2V73A	HP 730 300-ml Gray DesignJet Ink Cartridge HP 730 300-ml Photo Black DesignJet Ink Cartridge
Jse Original H	P inks and printheads, and HP large format printing materials, to experience
	h quality and reliable performance that enable less downtime. These critical rre designed and engineered together as an optimized printing system, and
)riginal HP inł	vs are designed to maximize the life of HP printheads. Protect your HP printer
risit hp.com/g	using Original HP inks for full HP warranty protection. For more information, o/OriginalHPinks.
)riginal HP lar	ge format printing materials
	ight White Inkjet Paper (FSC® certified) <sup>7</sup> (recyclable) <sup>8</sup> 914 mm x 91.4 m (36 in x
100 ft) 16980A HP Co	ated Paper (PEFC™ certified) <sup>7</sup> (recyclable) <sup>8</sup> 914 mm x 91.4 m (36 in x 300 ft)
.5C80A HP Ur	niversal Heavyweight Coated Paper, 3-in Core (FSC® certified) <sup>7</sup> (recyclable) <sup>8</sup> 914 (36 in x 300 ft)
	veryday Matte Polypropylene, 3-in Core 914 mm x 61 m (36 in x 200 ft)
or the entire	HP Large Format Printing Materials portfolio, please see HPLFMedia.com.
Service and Su	upport
	ll)/UB8U4E (2-roll) HP 3 year Next Business Day Onsite Hardware Support with
Defective Med JB9P7E (1-ro	ia Retention II)/UB8U5E (2-roll) HP 4 year Next Business Day Onsite Hardware Support with
Defective Med	ia Retention II)/UB8U6E (2-roll) HP 5 year Next Business Day Onsite Hardware Support with
Defective Med	ia Retention
	oll)/UB8U7PE (2-roll) HP 1 year Post Warranty Next Business Day Onsite port with Defective Media Retention
J1XV4E HP Pr	eventive Maintenance Service stallation Service with Network Setup
	Sugnation Service with Network Setup Support Services offer installation, maintenance, and extended support service
le.g. 2,3, 4 and	d 5 years). For more information, please visit hp.com/go/cpc
ECO highlights	5
<ul> <li>Save pap</li> </ul>	er with automatic print settings and image nesting
<ul> <li>ENERGY !</li> </ul>	STAR® certified <sup>1</sup> and EPEAT® registered <sup>2</sup>
<ul> <li>FSC<sup>®</sup>-cer</li> </ul>	venient HP ink cartridge recycling <sup>3</sup> tified papers <sup>4</sup> , recyclable HP media; some HP media eligible for take-back
program	
Please recycle website: http:/	large-format printing hardware and printing supplies. Find out how at our //www.hp.com/ecosolutions
	R and the ENERGY STAR mark are registered trademarks owned by the U.S. I Protection Agency.
EPEAT® regis	stered where applicable. EPEAT registration varies by country. See
<sup>8</sup> Program ava	peat.net for registration status by country. uilability varies. Please check http://www.hp.com/recycle for details.
BMG tradem	ark license code FSC®-C115319, see http://www.fsc.org. HP trademark license 17543, see http://www.fsc.org. Not all FSC®-certified products are available in
all regions. Fo	r information about HP large format printing materials, please visit
nttp://www.H Recyclable H	PLFMedia.com. IP papers can be recycled through commonly available recycling programs, or
according to re	egion-specific practices. Some HP media are eligible for return through the HP
	Media take-back program. Programs may not exist in your area. See PLFMedia.com/hp/ecosolutions for details.
	printing time. Printed in Fast mode with Economode on, using HP Bright White bond) and Original HP inks.
±0.1% of the	e specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50–609
Applicable fo	lity, on AO/E HP Matte Film in Best or Normal mode with Original HP inks or PostScript printers only.
Applicable for Based on 8 (	nr dual-roll printers only
BMG tradem ode FSC®-CO	ark license code FSC®-C115319, see http://www.tsc.org. HP trademark license 17543, see http://www.fsc.org. BMG trademark license code PEFC™/29-31-
61 see http:	//www.pefc.org_HP.trademark license.code.PEEC™/29-31-198_see
Can be recvo	fc.org. Not all FSC®- or PEFC™-certified products are available in all regions. led through commonly available recycling programs.





